

First edition date: October 15, 2003 Last revision date: 6-3-2017

Number of pages: 1

Technical Data Sheet

General

Article number: 9030##

Description: Colad Fine Line Tape



Specification

Backing properties: thermally stabilized PVC backing.

Adhesive: rubber based pressure sensitive adhesive.

Overall thickness: 0,137 mm (0,0054 inch).

Core: 76 mm (3 inch) plastic core.

Color: green (visual)
Tensile strength (nominal): 245 N/100 mm
Elongation at break: 150% ASTM-D-1000.

Sizes: 3 mm* x 55 m* (0,117* x 2165 inch*)

6 mm* x 55 m* (0,234* x 2165 inch*) 9 mm* x 55 m* (0,351* x 2165 inch*) 12 mm* x 55 m* (0,468* x 2165 inch*) 19 mm* x 55 m* (0,741* x 2165 inch*).

*width \pm 1 mm, length \pm 0,1 m.

Temperature resistance: takes a double bake at 130°C / 270°F.

Hazardous components: non, cadmium free.
Packing: per roll in a plastic bag

Shelf life: one year from date of receipt by customer when stored at 22°C (72°F)

and 50% relative humidity.

Remarks

- The product user should make his/her own tests to determine the product's suitability for the intend use and shall assume all risks and liability in connection therewith.
- Art.no. 9030## are used where a tape must meet a variety of paint masking applications.
- Recommended uses: preferred for medium to high temperature applications where a sharp fine line is required.
- Adheres to a wide variety of surfaces.
- This tape is designed to offer a high degree of conformability without excessive stretch.
- Colad Fine Line Tape 9030## will hold and cleanly remove from surfaces in the presence of 130°C temperatures for at least 30 minutes.
- Assures the user of a quick laydown, no residue on demask and a sharp, clean separate line.
- For the very straight (precise) masking of objects that have to be sprayed.
- For example for the spraying of more colors, printing of custom painting.
- Can also be used with water based paints.

Created by

EMM International BV The Netherlands www.emm.com



T +31(0)38 467 66 00

www.colad.co

